

CCFL INVERTER

(For Dual Tube Applications)

GENERAL DESCRIPTION

The AC3-12-1939 is designed to power 2 CCFLs to a nominal power level of 9.8 Watts from a +12V source.

Intensity control is accomplished by the user providing a DC voltage level at PIN 6 of CON1.

Enable control is accomplished at PIN 5 of CON1.

A +5V reference voltage is available at PIN 7 of CON1 for external use.

All outputs are open and short circuit protected.

MECHANICAL/ENVIRONMENTAL

Weight = 20 grams

Altitude = 10,000 ft max.

Humidity < 85% non-condensing


Size (L x W x H) = 5.4 IN x 0.7 IN x 0.357 IN

PCB thickness = 0.062 IN

Mounting Holes = 0.120 IN diameter (X2)

Input Power & Control Connector = CON1

CCFL Output Connectors = CON2 and CON3



INPUT CONNECTOR
CON1
MOLEX 53261-0890

PIN #	FUNCTION
1	-VIN(PWR)
2	-VIN(PWR)
3	GND(PWR)
4	GND(PWR)
5	ENABLE
6	INTENSITY CNTL
7	+5V REF OUT
8	TBD

OUTPUT CONNECTORS
CON2, CON3
JST SM03 4.0JB-BHS-1-TB

PIN #	FUNCTION
1	CCFL HOT
2	NC
3	CCFL COLD

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage (Referenced to Ground)	-0.7 to 14.0	Vdc
Vip	Voltage applied to any Input Pin (Referenced to Ground)	-0.7 to 5.7	Vdc
Iop	Current sourced or sinked from any Output Pin	+/- 10	mAdc
Pin	Input Power (DC Input Voltage x DC Input Current)	13.3	W
Top	Operating Temperature (Still air ambient around Inverter)	0 to +70	°C
Tstg	Storage Temperature	-40 to +105	°C

*Maximum Ratings are those values beyond which damage to the inverter may occur.

RECOMMENDED OPERATING CONDITIONS


Symbol	Parameter	Min	Max	Unit
Vin	Supply Voltage (Referenced to Ground)	10.8	13.2	Vdc
Lsv	Cold Cathode Fluorescent Lamp Sustaining Voltage	420	700	Vrms
Vcntl	Intensity Control Voltage	0	5	Vdc

ELECTRICAL CHARACTERISTICS

Vin = +12.0V, Lsv = 560Vrms, Vcntl = 0V, Enable = +5V unless otherwise specified.

Symbol	Parameter	Test Conditions	Min	Max	Unit
Lstart	Lamp Starting Voltage	Open Circuit	1750		Vrms
Lout	Lamp Output Current		7.8	9.6	mArms
Lfreq	Lamp-Current Frequency		38	47	KHz
Pfreq	PWM Dimming Frequency	Vcntl (PIN 6) = +2.5V	95	101	Hz
Pdc	PWM Duty Cycle Range	Vcntl (PIN 6) <= 0.25V		100	%
Pdc	PWM Duty Cycle Range	Vcntl (PIN 6) >= 4.9V	0		%
ENoff	Enable Control	unit OFF (Pin 5)		0.8	Vdc
ENon	Enable Control	unit ON (PIN 5)	2.0		Vdc
+5Vout	+5V Reference Out (PIN 7)	10K Load to Ground	4.6	5.25	Vdc
Iin	Input Current Draw			1.0	Adc
Eff	Electrical Efficiency		90		%

Display Brightness vs Vcntl



— — Zippy D00-8889-106

— AC3-12-1939