



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-2543

PRODUCT DATA SHEET

08/05/14

20.1" UXGA LED BACKLIT TFT DISPLAY

Sunlight Readability/1000:1 dimming/Cool operation

GENERAL DESCRIPTION

The ACD-2543 consists of the AUO M201UN02 V6 UXGA TFT display modified with a high performance LED backlight.


Customer Consigned Panel.

Performance at given brightness levels

900 cd/m² with 58.1 watts LED power

Display outline identical to standard CCFL equipped panel

For many applications, satisfies sunlight readability goals



LCD PANEL HIGHLIGHTS

20.1" TFT Active Matrix Color

408.0 (H) mm x 306.0 (V) mm viewable area

UXGA 1600 x 1200 pixels, 16.7M colors

1000:1 typical contrast ratio

Display Mode Normally Black

For complete LCD specification (standard panel), refer to LG M201UN02 V6 data sheet.

LED BACKLIGHT FEATURES

White LED edge-light rail

Two wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

1000:1 or better dimming ratio, guaranteed¹

¹ For best power transfer and control, use ACI-F090660-2495 LED driver. Do not set the driver output current (Ifwd) higher than the value specified in the Maximum Ratings table of this document. Please contact the factory for more specific use LED driver solutions if required.

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Top	Operating temperature of display (center of panel surface)	0 to +50	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	Display storage temperature	-20 to +60	Deg-C
Ifwd	Maximum LED edge-light forward current (DC)	49.5	mA

*Maximum Ratings are those values beyond which damage to the driver may occur

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd = 41.25mA per bank, LED rail ACR-0908-2542, 8 banks per rail, 2 rails per display, Ta = +25Deg-C, LCD powered

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bp	Panel Brightness		810	900	990	cd/m ²
X	White X coordinate			0.254		-
Y	White Y coordinate			0.268		-

LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS

Ifwd = 41.25mA per bank, 8 banks per rail, 2 rails per display, Top = +25Deg-C

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		80	88	96	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS

