



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-2590

PRODUCT DATA SHEET – PAGE 1 OF 3

8.4" XGA LED BACKLIT TFT DISPLAY WITH NVIS WHITE CAPABILITY

GENERAL DESCRIPTION


The ACD-2590 consists of the NEC NL10276BC16-06 XGA TFT display modified with a high performance LED backlight capable of Day and NVIS White.

Customer Consigned Panel

Performance at given brightness levels

1000 cd/m² with 8.8 watts LED power (Day)
4.8 cd/m² with 1.2 watts LED power (NVIS)

08/19/15



LED BACKLIGHT FEATURES

Day and NVIS LED edge-light rail

Three wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

5,000:1 or better dimming ratio (Day)¹

¹ For best power transfer and control, use one ACI-2596 Dual Mode LED Driver.

LCD PANEL HIGHLIGHTS

8.4" TFT Active Matrix Color

170.496 (H) mm x 127.872 (V) mm viewable area

XGA 1024 x 768 pixels, 16.8 M colors

600:1 typical contrast ratio

72% color gamut (NTSC color space)

Display Mode Normally Black

RoHS Compliant

For complete LCD specification (standard panel), refer to the NEC 10276BC16-06 datasheet

MAXIMUM RATINGS

08/19/15

Symbol	Parameter	Value	Unit
Top ¹	Operating temperature of display (center of panel surface)	-10 to +70	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg ¹	Display storage temperature	-30 to +80	Deg-C
Ifwd	LED forward current (Day)	120	mA
Ifwd	LED forward current (NVIS)	36	mA

*Maximum Ratings are those values beyond which damage may occur

¹Per Manufacturer's Specification

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd(Day) = 100mA per bank, 1 bank per rail, 1 rail per display, Ifwd(NVIS) = 30mA per bank, 1 bank per rail, 1 rail per display, LED rail: ACR-2567, Ta = +25Deg-C, LCD powered

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bpd	Panel Brightness (Day)		900	1000	1100	cd/m ²
Bpn	Panel Brightness (NVIS)		4.3	4.8	5.3	cd/m ²
Xd	White X coordinate (Day mode)			0.274		-
Yd	White Y coordinate (Day mode)			0.314		-
XN	White X coordinate (NVIS)			0.297		-
YN	White Y coordinate (NVIS)			0.483		-

LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS


Ifwd(Day) = 100mA, Ifwd(NVIS) = 30mA, Top = +25Deg-C

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop (Day mode)		79	88	97	Vdc
Vfwd	LED rail forward voltage drop (NVIS)		36	40	44	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS

08/19/15

Day mode



NVIS

