



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-2711

PRODUCT DATA SHEET

11/10/2015

21.5" FULL HD LED BACKLIT TFT DISPLAY

Sunlight Readability/1000:1 dimming/Cool operation

GENERAL DESCRIPTION

The ACD-2711 consists of the AUO G215HVN01.0 TFT display modified with a high performance LED backlight.


Customer Consigned Panel

Performance at given brightness levels

1000 cd/m² with 47.7 watts LED power

Display outline identical to standard LED equipped panel

For many applications, satisfies sunlight readability goals



LCD PANEL HIGHLIGHTS

21.5" TFT Active Matrix Color

476.64 (H) mm x 268.11 (V) mm viewable area

Full HD 1920 x 1080 pixels, 16.2M colors

5000:1 typical contrast ratio

Display Mode Normally Black

Physical Size 495.6(W)mm x 292.2(H)mm x 16.4(D)mm

For complete LCD specification (standard panel), refer to the AUO G215HVN01.0 data sheet.

LED BACKLIGHT FEATURES

White LED edge-light rail

Two wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

1000:1 or better dimming ratio, guaranteed¹

¹ For best power transfer and control, use two ACI-E110265-2712 LED drivers. Do not set the driver output current (Ifwd) higher than the value specified in the Maximum Ratings table of this document. Please contact the factory for more specific use LED driver solutions if required.

MAXIMUM RATINGS *

Symbol	Parameter	Value	Unit
Top ¹	Operating temperature of display (center of panel surface)	-0 to +60	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg ¹	Display storage temperature	-20 to +60	Deg-C
Ifwd	Maximum LED edge-light forward current (DC)	80	mA

* Maximum Ratings are those values beyond which damage to the driver may occur

¹ Per Manufacture's Specification

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd = 66.25mA per bank, LED rail ACR-0924-2700, 4 banks per rail, 2 rails per display, Ta = +25Deg-C, moving air (36.0 CFM), min 2hr soak



Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bp	Panel Brightness		900	1000	1100	cd/m ²
X	White X coordinate			0.264		-
Y	White Y coordinate			0.303		-

LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS

Ifwd = 66.25mA per bank, 4 banks per rail, 2 rails per display, Top = +25Deg-C


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		81	90	99	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS



² Moving air (36.0 CFM)

MECHANICAL CHARACTERISTICS (FRONT)



MECHANICAL CHARACTERISTICS (BACK)

