



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-2718

PRODUCT DATA SHEET

11/24/2015

17.0" SXGA LED BACKLIT TFT DISPLAY WITH NVIS CLASS B CAPABILITY

GENERAL DESCRIPTION


The ACD-2718 consists of the AUO G170EG01 V0 SXGA TFT display modified with a high performance LED backlight capable of Day and NVIS Class B operation.

Customer Consigned Panel

Performance at given brightness levels

1000 cd/m² with 42.0 watts LED power (Day)

9 cd/m² with 4.8 watts LED power (NVIS)



LCD PANEL HIGHLIGHTS

17.0" TFT Active Matrix Color

337.920 (H)mm x 270.336 (V)mm viewable area

SXGA 1280 x 3(RGB) x 1024 pixels, 16.2 M colors

1000:1 typical contrast ratio

Display Mode Normally White

Physical Size 358.5(W)mm x 296.5(H)mm x 15.8(D)mm

For complete LCD specification (standard panel), refer to the AUO G170EG01 V0 datasheet

LED BACKLIGHT FEATURES

Day and NVIS LED edge-light rail

Three wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

5000:1 or better dimming ratio (Day)¹

¹ For best power transfer and control, use 2 ACI ID5 Dual Mode LED Drivers (ACI-2719).



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-2718

PRODUCT DATA SHEET

11/24/2015

MAXIMUM RATINGS *

Symbol	Parameter	Value	Unit
Top ¹	Operating temperature of display (center of panel surface)	0 to +50	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg ¹	Display storage temperature	-20 to +60	Deg-C
Ifwd	LED forward current (Day)	120	mA
Ifwd	LED forward current (NVIS)	30	mA

*Maximum Ratings are those values beyond which damage may occur

1 Per Manufacturer's Specification

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd(Day) = 100mA per bank, 2 banks per rail, 2 rails per display, Ifwd(NVIS) = 25mA per bank, 1 bank per rail, 2 rails per display, LED rails: ACR-2387 Ta = +25Deg-C, moving air (36.0 CFM) min 2hr soak

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bpd	Panel Brightness (Day)		900	1000	1100	cd/m ²
Bpn	Panel Brightness (NVIS)		8.1	9	9.9	cd/m ²
Xd	White X coordinate (Day mode)			0.278		-
Yd	White Y coordinate (Day mode)			0.294		-
XN	White X coordinate (NVIS)			0.243		-
YN	White Y coordinate (NVIS)			0.735		-


LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS

Ifwd(Day) = 100mA, Ifwd(NVIS) = 25mA, Top = +25Deg-C




Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop (Day mode)		94	105	116	Vdc
Vfwd	LED rail forward voltage drop (NVIS)		87	97	107	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS

Day mode



NVIS



² Moving air (36.0 CFM)