



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACD-AU121-2805

PRODUCT DATA SHEET

10/18/2016

12.1" XGA LED BACKLIT TFT DISPLAY

Sunlight Readability/1000:1 dimming/Cool operation

GENERAL DESCRIPTION


The ACD-AU121-2805 consists of the AUO G121XN01 V0 XGA TFT display modified with a high performance LED backlight.

Performance at given brightness levels

1200 cd/m² with 10.0 watts LED power

Display outline identical to standard LED equipped panel

For many applications, satisfies sunlight readability goals



LCD PANEL HIGHLIGHTS

12.1" TFT Active Matrix Color

245.76 (H) mm x 184.32 (V) mm viewable area

XGA 1024 x 768 pixels, 16.2M/262K colors

700:1 typical contrast ratio

70% color gamut (NTSC color space)

Display Mode Normally White

For complete LCD specification (standard panel), refer to AUO G121XN01 V0 data sheet.

LED BACKLIGHT FEATURES

White LED edge-light rail

Two wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

1000:1 or better dimming ratio, guaranteed¹

¹ For best power transfer and control, use ACI-C170090-1979 LED driver. Do not set the driver output current (Ifwd) higher than the value specified in the Maximum Ratings table of this document. Please contact the factory for more specific use LED driver solutions if required.

MAXIMUM RATINGS *

Symbol	Parameter	Value	Unit
Top ¹	Operating temperature of display (center of panel surface)	-30 to +85	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg ¹	Display storage temperature	-30 to +85	Deg-C
Ifwd	Maximum LED edge-light forward current (DC)	108	mA

* Maximum Ratings are those values beyond which damage to the driver may occur

¹ Per Manufacture's Specification

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd = 90mA per bank, LED rail ACR-1101-2735, 1 bank per rail, 1 rail per display, Ta = +25Deg-C, moving air (36.0 CFM), min 2hr soak



Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bp	Panel Brightness		1080	1200	1320	cd/m ²
X	White X coordinate			0.323		-
Y	White Y coordinate			0.350		-

LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS

Ifwd = 90mA per bank, 1 bank per rail, 1 rail per display, Top = +25Deg-C

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		100	111	122	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS



² Moving air (36.0 CFM)