



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

ACD-AU190-2793

PRODUCT DATA SHEET

11/30/2020

19.0" SXGA LED BACKLIT TFT DISPLAY

Sunlight Readability/1000:1 dimming/Cool operation

GENERAL DESCRIPTION

The ACD-AU190-2793 consists of the AUO G190ETN01.2 SXGA TFT display modified with a high performance LED backlight.

Performance at given brightness levels

1450 cd/m² with 39.5 watts LED power

Display outline identical to standard LED equipped panel

For many applications, satisfies sunlight readability goals



LCD PANEL HIGHLIGHTS

19.0" TFT Active Matrix Color

376.32 (H) mm x 301.06 (V) mm viewable area

SXGA 1280 x 1024 pixels, 16.7M colors

1000:1 typical contrast ratio

70% color gamut (NTSC color space)

Display Mode Normally White

For complete LCD specification (standard panel), refer to AUO G190ETN01.2 data sheet.

LED BACKLIGHT FEATURES

White LED edge-light rail

Four wire connection (Typically 11 inches long), allows simple interconnect with LED driver¹

Projected lifetime > 75,000 hours

1000:1 or better dimming ratio, guaranteed¹

¹ For best power transfer and control, use ACI-F100420-2795 LED driver. Do not set the driver output current (Ifwd) higher than the value specified in the Maximum Ratings table of this document. Please contact the factory for more specific use LED driver solutions if required.

MAXIMUM RATINGS *

Symbol	Parameter	Value	Unit
Top ¹	Operating temperature of display (center of panel surface)	-30 to +85	Deg-C
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +90	Deg-C
Tstg ¹	Display storage temperature	-30 to +85	Deg-C
Ifwd	Maximum LED edge-light forward current (DC)	84	mA

* Maximum Ratings are those values beyond which damage to the driver may occur

¹ Per Manufacture's Specification

PANEL/BACKLIGHT OPTICAL CHARACTERISTICS

Ifwd = 70mA per bank, LED rail ACR-0943-2772, 3 banks per rail, 2 rails per display, Ta = +25Deg-C, moving air (36.0 CFM), min 2hr soak



Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Bp	Panel Brightness		1305	1450	1595	cd/m ²
X	White X coordinate			0.298		-
Y	White Y coordinate			0.338		-

LED EDGE-LIGHT ELECTRICAL CHARACTERISTICS

Ifwd = 70mA per bank, 3 banks per rail, 2 rails per display, Top = +25Deg-C

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		85	94	103	Vdc

TYPICAL LCD/LED BACKLIGHT PERFORMANCE GRAPHS



² Moving air (36.0 CFM)