



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACI-2873

PRODUCT DATA SHEET

08/16/17

I-DRIVE 6, 38.5 WATT LED DRIVER (77V, Single Channel, 0-500mA)

GENERAL DESCRIPTION

The ACI-F077500-2659 represents the 6th generation of I-Drive technology used for powering LED backlights.

Operating as a true constant current source and capable of driving a single bank of series connected LEDs with a forward voltage drop up to 77V. This driver provides a complete integrated solution that is regulated over an input voltage range from +10.8V to +15V DC.

Simple to connect and operate, this driver solution is capable of providing precise control to support dimming applications with a minimum of 3000:1.

This unit features enable and intensity control inputs.

MECHANICAL/ENVIRONMENTAL

Weight = 50.7 grams

Altitude = 35,000 ft max.

Humidity < 95% non-condensing

Size (L x W x H) = 5.00 IN x 2.00 IN x 0.540 IN

PCB thickness = 0.062 IN


Mounting Holes = 0.128 IN diameter (X2)

Input Power & Control Connector = CON1

LED Output Connector = CON2

Specified Components secured with 3M DP190 Gray Epoxy

RoHS Compliant



MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage (Referenced to Ground)	-0.7 to 20	Vdc
Vip	Voltage applied to any Input Pin (Referenced to Ground)	-0.7 to 5.7	Vdc
Iop	Current sourced or sinked from any Output Control Pin	+/- 10	mAdc
Pin	Input Power (DC Input Voltage x DC Input Current)	49	W
Top	Operating Temperature (Still air ambient around Driver)	-30 to +70	°C
Tstg	Storage Temperature	-40 to +105	°C

*Maximum Ratings are those values beyond which damage to the driver may occur.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
Vin	Supply Voltage (Referenced to Ground)	10.8	15.0	Vdc
Vf	Series Connected Cumulative LED Forward-Drop Voltage	**Vin + 1	77	Vdc
Icntl	LED Intensity Control Voltage	0.25	4.75	Vdc


**Vin must be less than the minimum Forward-Drop Voltage (Vf).

ELECTRICAL CHARACTERISTICS

Vin = +12.0V, Vf = 77V, Icntl = +4.75V, Enable = +5V, unless otherwise specified.

Symbol	Parameter	Test Conditions	Min	Nom	Max	Unit
OCV	Open Circuit Voltage	No Load	78	82	87	Vdc
Iout	Output Current		475	500	525	mAdc
Iadj	Nominal Output Current Adjust Range	Icntl(Pin 10) <= 0.25V	0			mAdc
		Icntl(Pin 10) >= 4.75V			500	mAdc
ENoff	Enable Control, Unit Off				0.5	Vdc
ENon	Enable Control, Unit ON		2.0			Vdc
+5Vref	+5V Output Reference Voltage	1K Ohm Load to Ground (Pin 13)	4.75	5.0	5.25	Vdc
Iin	Input Current Draw			3.7		Adc
Iind	Input Current Draw (Disabled)	Enable (Pin 9) = 0V			0.06	Adc
Eff	Electrical Efficiency			87		%

BRIGHTNESS CURVE



INPUT AND OUTPUT CONNETOR PIN ASSIGNMENTS

INPUT CONNECTOR CON1 MOLEX 87438-1443		OUTPUT CONNECTOR CON2 MOLEX 53261-1071	
PIN#	FUNCTION	PIN#	FUNCTION
1	+10.8 to +15.0V (PWR)	1	+LED (ANODE)
2	+10.8 to +15.0V (PWR)	2	NC
3	+10.8 to +15.0V (PWR)	3	NC
4	+10.8 to +15.0V (PWR)	4	NC
5	GND (PWR)	5	NC
6	GND (PWR)	6	-LED (CATHODE)
7	GND (PWR)	7	NC
8	GND (PWR)	8	NC
9	ENABLE	9	NC
10	ICNTL	10	NC
11	TBD		
12	TBD		
13	+5VDC REF OUT		
14	GND (SIGNAL OUT)		