



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACI-2934

PRODUCT DATA SHEET

11/15/18

I-DRIVE 2, 3.6 WATT LED DRIVER

(Single Channel, 20V, 0-180mA)

GENERAL DESCRIPTION

The ACI-2934 operates as a true constant current source and is capable of driving series connected LEDs with a forward voltage drop up to 20V. This driver provides a complete integrated solution that performs over an input voltage range from +4.75 to +5.25VDC.

Simple to connect and operate, this driver solution is capable of providing precise control to support wide dimming applications.

This unit features enable and intensity control inputs.

MECHANICAL/ENVIRONMENTAL

Weight = 10 grams

Altitude = 35,000 ft max.

Humidity < 95% non-condensing

Size (L x W x H) = 2.28 IN x 1.43 IN x 0.220 IN

Size (L x W x H) = 57.9mm x 36.3mm x 5.59mm

PCB thickness = 0.047 IN


Mounting Holes = 0.126 IN diameter (X2)

Input Power & Control Connector = CON1

LED Output Connector = CON2

Specified Components secured with 3M DP-190 Epoxy

RoHS Compliant



INPUT CONNECTOR CON1		OUTPUT CONNECTOR CON2	
MOLEX 53261-0871		MOLEX 53261-0871	
PIN#	FUNCTION	PIN#	FUNCTION
1	+4.75 to +5.25V	1	+ LED (ANODE)
2	+4.75 to +5.25V	2	NC
3	GND (PWR)	3	NC
4	GND (PWR)	4	NC
5	ENABLE	5	- LED (CATHODE)
6	ICNTL / PWM	6	NC
7	NC	7	NC
8	GND (SIGNAL)	8	NC

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage (Referenced to Ground)	-0.7 to 6.0	Vdc
Vip	Voltage applied to any Input Pin (Referenced to Ground)	-0.7 to 5.7	Vdc
Iop	Current sourced or sinked from any Output Control Pin	+/- 10	mAdc
Pin	Input Power (DC Input Voltage x DC Input Current)	4.8	W
Top	Operating Temperature (Still air ambient around Driver)	-30 to +85	°C
Tstg	Storage Temperature	-40 to +105	°C

*Maximum Ratings are those values beyond which damage to the driver may occur.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
Vin	Supply Voltage (Referenced to Ground)	4.75	5.25	Vdc
Vf	Series Connected Cumulative LED Forward-Drop Voltage	**Vin + 1	20	Vdc
Icntl	LED Intensity Control Voltage	0.1	4.75	Vdc
PWMcntl	Intensity Control PWM Duty-Cycle Range (User Supplied Input)	0	100	%
PWMfreq	Intensity Control PWM Frequency Range (User Supplied Input)	100	1000	Hz

**Vin must be less than the minimum Forward-Drop Voltage (Vf).

ELECTRICAL CHARACTERISTICS

Vin = +5V, Vf = 20V per channel, # of channels = 1, Icntl = +4.75V, Enable = +5V, unless otherwise specified.

Symbol	Parameter	Test Conditions	Min	Nom	Max	Unit
OCV	Open Circuit Voltage	No Load	22	24	26	Vdc
Iout	Output Current per Channel		171	180	189	mAdc
Iadj	Nominal Output Current Adjust Range Per Channel	Icntl(Pin 6) ≤ +0.10V or PWMcntl(Pin 6) = 0%	0			mAdc
		Icntl(Pin 6) ≥ +4.75V or PWMcntl(Pin 6) = 100%			180	mAdc
PWMhi	PWM High Signal Level (V _{IH})		4.75			Vdc
PWMlo	PWM Low Signal Level (V _{IL})				0.1	Vdc
ENoff	Enable Control, Unit Off				0.5	Vdc
ENon	Enable Control, Unit ON		2.0			Vdc
Iin	Input Current Draw			0.825		Adc
Iind	Input Current Draw (Disabled)	Enable (Pin 5) = 0V			0.06	Adc
Eff	Electrical Efficiency			87		%

BRIGHTNESS CURVE

