

ACI-2944

PRODUCT DATA SHEET

07/27/18

I-DRIVE 5, 28.8 WATT LED DRIVER (Eight Channel, 120V, 0-30mA per Channel)

GENERAL DESCRIPTION

The ACI-2944 represents the 5th generation of I-Drive technology used for powering LED backlights.

Operating as a true constant current source and capable of driving up to 8 banks of series connected LEDs with a forward voltage drop up to 120V. This driver provides a complete integrated solution that is regulated over an input voltage range from +24V to +30V.

Simple to connect and operate, this driver solution is capable of providing precise control to support dimming applications with a minimum of 3000:1.

This unit features enable and intensity control inputs.

MECHANICAL/ENVIRONMENTAL

Weight = 35.7 grams

Altitude = 35,000 ft max.

Humidity < 95% non-condensing

Size (L x W x H) = 3.25 IN x 2.00 IN x 0.47 IN


PCB thickness = 0.062 IN

Mounting Holes = 0.128 IN diameter (X2)

Input Power & Control Connector = CON1

LED Output Connectors = CON2 and CON3

RoHS Compliant



INPUT CONNECTOR
CON1
MOLEX 53261-1471

OUTPUT CONNECTOR
CON2
MOLEX 53261-0871

PIN# FUNCTION

1	+24.0 to +30.0V (PWR)
2	+24.0 to +30.0V (PWR)
3	+24.0 to +30.0V (PWR)
4	+24.0 to +30.0V (PWR)
5	GND (PWR)
6	GND (PWR)
7	GND (PWR)
8	GND (PWR)
9	ENABLE
10	ICNTL
11	TBD
12	TBD
13	+5VDC REF OUT
14	GND (SIGNAL)

PIN# FUNCTION

1	+ LED (ANODE)
2	+ LED (ANODE)
3	+ LED (ANODE)
4	+ LED (ANODE)
5	- LED (CATHODE 1 - Vf)
6	- LED (CATHODE 2 - Vf)
7	- LED (CATHODE 3 - Vf)
8	- LED (CATHODE 4 - Vf)

OUTPUT CONNECTOR
CON3
MOLEX 53261-0871

PIN# FUNCTION

1	+ LED (ANODE)
2	+ LED (ANODE)
3	+ LED (ANODE)
4	+ LED (ANODE)
5	- LED (CATHODE 5 - Vf+3)
6	- LED (CATHODE 6 - Vf+3)
7	- LED (CATHODE 7 - Vf+3)
8	- LED (CATHODE 8 - Vf+3)

MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage (Referenced to Ground)	-0.7 to 32	Vdc
Vip	Voltage applied to any Input Pin (Referenced to Ground)	-0.7 to 5.7	Vdc
Iop	Current sourced or sinked from any Output Control Pin	+/- 10	mAdc
Pin	Input Power (DC Input Voltage x DC Input Current)	37.3	W
Top	Operating Temperature (Still air ambient around Driver)	-30 to +85	°C
Tstg	Storage Temperature	-40 to +105	°C

*Maximum Ratings are those values beyond which damage to the driver may occur.

RECOMMENDED OPERATING CONDITIONS


Symbol	Parameter	Min	Max	Unit
Vin	Supply Voltage (Referenced to Ground)	24.0	30.0	Vdc
Vf ¹ (CON2)	Series Connected Cumulative LED Forward-Drop Voltage	**Vin + 1	117	Vdc
Vf ² (CON3)	Series Connected Cumulative LED Forward-Drop Voltage	Vf ¹ + 3	120	Vdc
Icntl	LED Intensity Control Voltage	0.25	4.75	Vdc

**Vin must be less than the minimum Forward-Drop Voltage (Vf).

ELECTRICAL CHARACTERISTICS

Vin = +28V, Vf = 120V per channel, # of channels = 8, Icntl = +4.75V, Enable = +5V unless otherwise specified.


Symbol	Parameter	Test Conditions	Min	Nom	Max	Unit
OCV	Open Circuit Voltage	No Load	125	135	145	Vdc
Iout	Output Current		28.5	30	31.5	mAdc
Iadj	Nominal Output Current Adjust Range	Icntl(Pin 10) = +0.25V to +4.75V	0		30	mAdc
ENoff	Enable Control, Unit Off				0.5	Vdc
ENon	Enable Control, Unit ON		2.0			Vdc
+5Vref	+5V Output Reference Voltage	1K Ohm Load to Ground (Pin 13)	4.75	5.0	5.25	Vdc
Iin	Input Current Draw			1.21		Adc
Iind	Input Current Draw (Disabled)	Enable (Pin 9) = 0V			0.06	Adc
Eff	Electrical Efficiency			85		%



ACI-2944

PRODUCT DATA SHEET

07/27/18



CONNECTION DIAGRAM