

397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

I-DRIVE 2, 12 WATT LED DRIVER

(20V, 1 Channel, 0-600mA)

GENERAL DESCRIPTION

The ACI-3195 operates as a true constant current source and is capable of driving up to 1 bank of series connected LEDs with a forward voltage drop up to 20V. This driver provides a complete integrated solution that is regulated over an input voltage range from +10 to +15VDC.

Simple to connect and operate, this driver solution is capable of providing precise control to support wide dimming applications.

This unit features enable and intensity control inputs.

MECHANICAL/ENVIRONMENTAL

Weight = 10 grams

Altitude = 35,000 ft max.

Humidity < 95% non-condensing

Size (L x W x H) = 2.28 IN x 1.43 IN x 0.220 IN

Size (L x W x H) = 57.9mm x 36.3mm x 5.59mm

PCB thickness = 0.047 IN

Mounting Holes = 0.126 IN diameter (X2)

Input Power & Control Connector = CON1


LED Output Connector = CON2

RoHS Compliant

ACI-3195

PRODUCT DATA SHEET

08/18/22



MAXIMUM RATINGS*

Symbol	Parameter	Value	Unit
Vin	Supply Voltage (Referenced to Ground)	-0.7 to 18	Vdc
Vip	Voltage applied to any Input Pin (Referenced to Ground)	-0.7 to 5.7	Vdc
Iop	Current sourced or sinked from any Output Control Pin	+/- 10	mAdc
Pin	Input Power (DC Input Voltage x DC Input Current)	15.9	W
Top	Operating Temperature (Still air ambient around Driver)	-40 to +85	°C
Tstg	Storage Temperature	-40 to +105	°C

*Maximum Ratings are those values beyond which damage to the driver may occur.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
Vin	Supply Voltage (Referenced to Ground)	10.0	15.0	Vdc
Vf	Series Connected Cumulative LED Forward-Drop Voltage	**Vin + 1	20	Vdc
Icctl	LED Intensity Control Voltage	0.25	4.75	Vdc
PWMcctl	Intensity Control PWM Duty-Cycle Range (User Supplied Input)	0	100	%
PWMfreq	Intensity Control PWM Frequency Range (User Supplied Input)	100	1000	Hz

**Vin must be less than the minimum Forward-Drop Voltage (Vf).

ELECTRICAL CHARACTERISTICS

Vin = +12V, Vf = 20V per channel, # of channels = 1, Icctl = +4.75V, Enable = +5V, unless otherwise specified.

Symbol	Parameter	Test Conditions	Min	Nom	Max	Unit
OCV	Open Circuit Voltage	No Load	46	48	50	Vdc
Iout	Output Current		570	600	630	mAdc
Iadj	Nominal Output Current Adjust Range Per Channel	Icctl(Pin 6) ≤ +0.25V or PWMcctl(Pin 6) = 0%	0			mAdc
		Icctl(Pin 6) ≥ +4.75V or PWMcctl(Pin 6) = 100%			600	mAdc
PWMhi	PWM High Signal Level (V _{IH})		4.75			Vdc
PWMlo	PWM Low Signal Level (V _{IL})				0.25	Vdc
ENoff	Enable Control, Unit Off				0.5	Vdc
ENon	Enable Control, Unit ON		2.0			Vdc
+5Vref	+5V Output Reference Voltage	1K Ohm Load to Ground (Pin 7)	4.75	5.0	5.25	Vdc
Iin	Input Current Draw			1.15		Adc
Iind	Input Current Draw (Disabled)	Enable (Pin 5) = 0V			0.06	Adc
Eff	Electrical Efficiency			87		%

BRIGHTNESS CURVE

