



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

ACR-0772-3183

PRODUCT DATA SHEET

11.77" DUAL MODE LED RAIL

(Day LEDs: Dual Bank, 77V @ 70mA)

04/14/2022

GENERAL DESCRIPTION

The ACR-3183 is designed as a replacement for 13.3" LED displays.

The rail uses high performance LEDs

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 3 grams

Altitude = 35,000 Ft maximum


Humidity < 95% non-condensing

Size (L x W x H) = 11.77 IN x 0.115 IN x .032 IN

Flex Foil thickness = 0.007 IN

Input connector = CON1

RoHS compliant



397 Route 281
Tully, New York 13159
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET

MAXIMUM RATINGS

04/14/2022

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED forward current (DC)	92	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 150mA	87	93		lm
X	White X coordinate			0.280		
Y	White Y coordinate			0.295		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 70mA (2 banks per rail), Tled = +75Deg-C (LED's with heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		69	77	85	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

