



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

ACR-0862-2407

PRODUCT DATA SHEET - PAGE 1 OF 2

10.04" DUAL BANK LED RAIL

(Dual Bank, 86V @ 70mA)

03/16/2021

GENERAL DESCRIPTION

The ACR-0862-2407 is designed as a replacement for field replaceable, single rail, single edge lit 12.1" LED displays.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 5 grams

Altitude = 35,000 Ft maximum


Humidity < 95% non-condensing

Size (L x W x H) = 10.04 IN x 0.175 IN x .072 IN

PCB thickness = 0.032 IN

Input connector = CON1

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET - PAGE 1 OF 2

MAXIMUM RATINGS

03/16/2021

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED forward current (DC)	84	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 93mA	14.1	11	18.1	cd
X	White X coordinate			0.270		
Y	White Y coordinate			0.240		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 70mA per bank, 2 banks per rail, Tled = +75Deg-C (LED's without heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		78	86	94	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

