



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACR-0864-2834

PRODUCT DATA SHEET – PAGE 1 OF 2

19.08" QUAD BANK LED RAIL

(Quad Bank, 86V @ 43.75mA)

04/17/17

GENERAL DESCRIPTION

The ACR-0864-2834 is designed as a replacement for 21.5" LED displays.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 2 grams


Altitude = 35,000 Ft maximum

Humidity < 95% non-condensing

Size (L x W x H) = 19.08 IN x 0.130 IN x .047 IN

PCB thickness = 0.007 IN

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET – PAGE 2 OF 2

MAXIMUM RATINGS

04/17/17

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-40 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +85	Deg-C
Ifwd	LED forward current	53	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Iv	Luminance Intensity Rank	Ifwd = 110mA	9	11	13	cd
X	White X coordinate			0.299		-
Y	White Y coordinate			0.289		-

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 43.75mA (4 Banks per Rail, 2 Rails per Display), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		77	86	95	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

