



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACR-0943-2813

PRODUCT DATA SHEET – PAGE 1 OF 2

15.36" TRI BANK LED RAIL

(Tri Bank, 94V @ 70mA)

11/10/16

GENERAL DESCRIPTION

The ACR-0943-2813 is designed as a replacement for 19" LED displays.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 2 grams


Altitude = 35,000 Ft maximum

Humidity < 95% non-condensing

Size (L x W x H) = 15.36 IN x 0.155 IN x .047 IN

PCB thickness = 0.007 IN

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET – PAGE 2 OF 2

MAXIMUM RATINGS

11/10/16

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	LED forward current	84	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Iv	Luminance Intensity Rank	Ifwd = 110mA	9	11	13	cd
X	White X coordinate			0.299		-
Y	White Y coordinate			0.289		-

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 70mA (3 Banks per Rail, 1 Rail per Display), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		85	94	103	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

