



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACR-0966-2607

PRODUCT DATA SHEET – PAGE 1 OF 2

15.00" SIX BANK LED RAIL

(Six Bank, 96V @ 38.3mA)

1/8/15

GENERAL DESCRIPTION

The ACR-0966-2607 is designed as a replacement for the tri tube, dual edge lit 19.0" CCFL displays.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 11 grams


Altitude = 35,000 Ft maximum

Humidity < 95% non-condensing

Size (L x W x H) = 15.000 IN x 0.325 IN x .072 IN

PCB thickness = 0.032 IN

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET – PAGE 2 OF 2

MAXIMUM RATINGS

1/8/15

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED edge-light forward current (DC)	46	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Iv	Luminance Intensity Rank	Ifwd = 93mA	16.5	-	17.3	cd
Cx	White X coordinate			0.245		-
Cy	White Y coordinate			0.220		-

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 38.3mA, Tled = +75Deg-C (LED's without heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		86	96	106	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

