



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

ACR-2498

PRODUCT DATA SHEET – PAGE 1 OF 3

20.83" DUAL MODE LED RAIL

(Day LEDs: Quad Bank, 84V @ 75mA)
(NVIS LEDs: Dual Bank, 85V @ 25mA)

5/12/14

GENERAL DESCRIPTION

The ACR-2498 is designed as a replacement for dual rail, dual edge lit 19" LED displays.

The rail uses high performance LEDs capable of Day and NVIS Class B operations.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's dual mode I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 6 grams

Altitude = 35,000 Ft maximum


Humidity < 95% non-condensing

Size (L x W x H) = 20.8300 IN x 0.380 IN x .097 IN

Flex PCB thickness = 0.007 IN

Input connector = CON1

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET – PAGE 2 OF 3

DAY MODE

MAXIMUM RATINGS

5/12/14

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED forward current (DC)	90	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 93mA		21.4		cd
X	White X coordinate			0.265		
Y	White Y coordinate			0.260		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 75mA (4 bank per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		76	84	92	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Fax: 315 696 9923
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET – PAGE 3 OF 3

NVIS MODE

MAXIMUM RATINGS

5/12/14

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-40 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +85	Deg-C
Ifwd	Maximum LED forward current (DC)	30	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 20mA			200	mcd
X	White X coordinate			0.302		
Y	White Y coordinate			0.676		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 25mA (2 bank per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		77	85	93	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

