



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

ACR-3169

PRODUCT DATASHEET

15.65" DUAL MODE LED RAIL

(Day LEDs: Quad Bank, 71V @ 53.75mA)
(NVIS LEDs: Dual Bank, 90V @ 25mA)

03/03/2022

GENERAL DESCRIPTION

The ACR-3169 is designed as a replacement for dual rail, dual edge lit 17.3" LED displays.

The rail uses high performance LEDs capable of Day and NVIS White operations.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's dual mode I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 6 grams

Altitude = 35,000 Ft maximum


Humidity < 95% non-condensing

Size (L x W x H) = 15.65 IN x 0.370 IN x 0.097 IN

Flex PCB thickness = 0.007 IN

Input connector = CON1

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATASHEET

DAY MODE

MAXIMUM RATINGS

03/03/2022

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED forward current (DC)	64.5	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 93mA		21.4		cd
X	White X coordinate			0.265		
Y	White Y coordinate			0.260		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 53.75mA (4 banks per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		64	71	78	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATASHEET

NVIS MODE

MAXIMUM RATINGS

03/03/2022

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-40 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +85	Deg-C
Ifwd	Maximum LED forward current (DC)	30	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 20mA			200	mcd
X	White X coordinate			0.260		
Y	White Y coordinate			0.280		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 25mA (2 banks per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		81	90	99	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

