



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

ACR-3205

PRODUCT DATA SHEET

9.52" DUAL MODE LED RAIL

(Day LEDs: Dual Bank, 60V @ 80mA)
(NVIS LEDs: Single Bank, 59V @ 30mA)

8/8/2022

GENERAL DESCRIPTION

The ACR-3205 is designed as a replacement for edge lit 10.6" LED displays.

The rail uses high performance LEDs capable of Day and NVIS White operations.

The rail requires the use of a constant current source to properly drive the LED's.

The LED rail is compatible with any of ACI's I-Drive series of LED Drivers.

MECHANICAL / ENVIRONMENTAL

Weight = 8 grams

Altitude = 35,000 Ft maximum


Humidity < 95% non-condensing

Size (L x W x H) = 9.52 IN x 0.175 IN x 0.064 IN

Flex Foil Thickness = 0.007 IN

Input connector = CON1

RoHS compliant



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET

DAY MODE

MAXIMUM RATINGS

8/8/2022

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +100	Deg-C
Ifwd	Maximum LED forward current (DC)	96	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 150mA	87	93		lm
X	White X coordinate			0.260		
Y	White Y coordinate			0.270		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 80mA per bank (2 banks per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		54	60	66	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS



397 Route 281
Tully, New York 13159-1175
Phone: 315 696-6676
Email: sales@acipower.com
www.acipower.com

PRODUCT DATA SHEET

NVIS MODE

MAXIMUM RATINGS

8/8/2022

Symbol	Parameter	Value	Unit
Tled	Operating temperature of LED edge light (light rail contact)	-30 to +85	Deg-C
Tstg	LED Rail storage temperature	-40 to +85	Deg-C
Ifwd	Maximum LED forward current (DC)	30	mA

LED OPTICAL CHARACTERISTICS

LED Manufacturer specifications for reference purpose only

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
BL	LED Brightness	Ifwd = 25mA			200	mcd
X	White X coordinate			0.280		
Y	White Y coordinate			0.320		

LED RAIL ELECTRICAL CHARACTERISTICS

Ifwd = 30mA per bank (1 bank per rail), Tled = +75Deg-C (LED's heat sinking to the display)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Vfwd	LED rail forward voltage drop		53	59	65	Vdc

TYPICAL LED RAIL PERFORMANCE GRAPHS

